

MX-AOK iT Series

LED Parking Lot / Area Light

SPECIFICATIONS



Model Number	MX-AOK-110WiT	MX-AOK-150WiT
Power consumption	110W	150W
Maximum Current	AC 1.25A (max.)	AC 1.67A (max.)
Driver/Efficiency	Meanwell HLG Series, >93%	Meanwell HLG Series, >94%
Luminous Flux	Lumen tolerance +/- 5% 14,300lm	Lumen tolerance +/- 5% 19,500lm
Lumens per watt	130	
Voltage	100-240/277VAC, 50/60Hz	
	277-528VAC, 50/60Hz	
Power Factor	>0.95	
CRI	Ra>70/80	
Colour Temperatures	3000-6500K	
Beam Angle Options	70°/130° / 75°/150° / 120°	
IP Rating	IP66	
Life Expectancy	50,000 hrs	
Heat Radiator	Anodized Aluminium	
Lens Material	PC	
Fixture Dimension	560*278*75mm	
Net Weight	5.6kg	
Carton Dimensions	700*390*170mm	
Gross Weight	6.7kg	
Warranty	5 years	
Certificate	UL, FCC, SAA, CE-EMC, CE-LVD, EMC, RoHS	

- Specialised design for outdoor parking lots, wide areas, billboard lighting
- Multiple bracket options for mounting: Bracket Type A (Slip Fitter); Bracket Type B (Direct Arm Mount); Bracket Type C (Trunnion Mount); Bracket Type D (Yoke Mount); Bracket Type E (Square/Round Pole Mount)
- Microwave and daylight sensors optional
- Dimming functions: 1-10V/PWM/Resistance/Timer/DALI dimmable driver available
- Black or brown finish
- Fishbone style high efficiency heat sink
- Black/brown colour fixtures available